

(800) 621-3914

hydraulics@generaltruckparts.com

MUNCIE POWER PRODUCTS PTOs, PUMPS & HYDRAULIC COMPONENTS



**Muncie®
Power
Products**

General Truck Parts is your trusted source for Muncie Power Products PTOs, hydraulic pumps, dump pumps, valves, controls and replacement hydraulic components.

MUNCIE HEAVY-DUTY PTO SERIES COMPARISON	TG6 SERIES	TG8 SERIES	CS6 SERIES	CS8 SERIES	A20 SERIES	A30 SERIES	A40 SERIES
FEATURE							
TRANSMISSION TYPE	Manual	Manual	Manual	Manual	Allison Automatic	Allison Automatic	Allison Automatic
TYPICAL TRUCK CLASS	Class 5–8	Class 6–8	Class 6–8	Class 7–8	Medium-Duty	Heavy-Duty	Heavy-Duty
MAX INTERMITTENT TORQUE	Up to 300 lb-ft	Up to 400 lb-ft	Up to 500 lb-ft	Up to 600 lb-ft	Up to 250 lb-ft	Up to 330 lb-ft	Up to 646 lb-ft
PUMP MOUNT OPTIONS	SAE B	SAE B	SAE B / BB	SAE B / BB	SAE B	SAE B / BB	SAE B / BB / C
PUMP MOUNT CAPABILITY	✓ Direct Mount & Remote Mount	✓ Direct Mount & Remote Mount	✓ Direct Mount & Remote Mount	✓ Direct Mount & Remote Mount	✓ Direct Mount & Remote Mount	✓ Direct Mount & Remote Mount	✓ Direct Mount & Remote Mount
SHIFT OPTIONS	Air	Air	Air	Air	Electric	Electric / Air	Electric
GEAR RATIO RANGE	0.70:1 – 1.67:1	0.70:1 – 1.67:1	0.55:1 – 1.70:1	0.55:1 – 1.70:1	0.62:1 – 1.29:1	0.62:1 – 1.29:1	0.63:1 – 1.24:1
CONTINUOUS DUTY	✓ Yes	✓ Yes	✓ Yes	✓ Yes	✓ Yes	✓ Yes	✓ Yes
TYPICAL PUMP FLOW CAPABILITY	Medium	Medium-High	High	High	Medium	High	Very High
BEST FOR	General Vocational	Medium-Heavy Vocational	High Torque Applications	Heavy Fleet Service	Allison Medium Duty Trucks	Allison High HP Applications	Severe-Duty Allison Applications

MUNCIE HYDRAULIC PUMP SERIES COMPARISON	PK SERIES	PF4 SERIES	PL SERIES
FEATURE			
PUMP TYPE	Gear Pump	Gear Pump	Gear Pump
CONSTRUCTION	Cast Iron	Cast Iron	Cast Iron
MOUNTING STANDARD	SAE B 2-Bolt	SAE B 2-Bolt	SAE B 2-Bolt
ROTATION	✓ Bi-Rotational Models Available	✓ Bi-Rotational Models Available	✓ Bi-Rotational Models Available
TYPICAL FLOW RANGE	15 – 85 GPM	5 – 45 GPM	30 – 95 GPM
MAX CONTINUOUS PRESSURE	3,500 PSI	3,500 PSI	3,500 PSI
PEAK PRESSURE	4,000 PSI	4,000 PSI	4,000 PSI
BEARING DESIGN	Heavy-Duty Roller Bearings	Heavy-Duty Roller Bearings	Heavy-Duty Roller Bearings
SEAL DESIGN	High-Pressure Lip Seal	High-Pressure Lip Seal	High-Pressure Lip Seal
CONTINUOUS DUTY RATED	✓ Yes	✓ Yes	✓ Yes
AVAILABLE PORTS	NPT & SAE O-Ring	NPT & SAE O-Ring	NPT & SAE O-Ring
IDEAL PTO MATCH	TG6, TG8, CS6, CS8, A30	TG6, TG8, A20, A30	CS8, CS10, CS11
BEST FOR	High-Flow Hydraulic Systems	General Vocational Service	Maximum Flow Applications



(800) 621-3914

4040 W. 40th Street
Chicago, IL 60632

info@generaltruckparts.com

QUALITY • EXPERIENCE • TRUST

www.generaltruckparts.com